

Product information for the building certification scheme BREEAM® (Building Research Establishment's Environmental Assessment Method)

The intention of this document is to support the BREEAM certification process by providing product specific information. The basis of this information is the BREEAM technical manual (2014)¹.

EVALON® V loose laid under ballast, mechanically fastened or bonded

General Information

Company name:	alwitra GmbH & Co. Klaus Göbel
Address:	Am Forst 1,54296 Trier
Contact person:	Herr Löcherbach
Phone:	+49 651 - 9102 - 0
Email:	alwitra@alwitra.de
Homepage:	www.alwitra.de
Date of this document:	14.12.2015

Product information

Product description

EVALON® V are bitumen compatible EVAC (ethylene vinyl acetate copolymer) waterproofing membrane systems. The product consists of a high polymer alloy of EVA (ethylene vinyl acetate) terpolymer and PVC (polyvinyl chloride) including additives. The waterproofing membranes are manufactured with a polyester fleece backing in a calendaring process. Seam welding is carried out with hot air or a solvent-based welding agent. EVALON® V (with polyester fleece backing) is also used as the basis for the multifunctional roofing membranes EVALON® Solar. In this case, on the upper side of the membrane, additional photovoltaic (PV) modules are factory-integrated to be connected via factory-mounted waterproof connection boxes and cables on the underside.

Application

EVALON® V can be applied in one layer for waterproofing of non-used and used flat and low slope roofs. Depending on specification, the membranes are applied as follows:

- loose laid under ballast (e. g. gravel, tiles, vegetation)
- mechanically fastened or
- bonded.

¹BREEAM UK New Construction non-domestic buildings technical manual 2014; Reference: SD5076 – Issue: 1.0; Date: 21/05/2014, www.breeam.org

Product sustainability fact sheet

EVALON® V can also be applied in one layer for waterproofing of non-waterproof foundations or other constructional elements to protect against ground moisture and non-pressing water (as a dampproofing system). Depending on specification, the membranes can be applied as follows:

- loose laid under ballast
- bonded

Technical data

Name	Value	Unit
Max. tensile force according to EN 12311-2 (A)	500	N/50mm
Elongation at max. tensile force according to EN 12311-2 (A)	60	%
Peel resistance of the seam joint according to EN 12316-2	150	N/50mm
Shear resistance of the seam joint according to EN12317-2	400	N/50mm
Tear propagation resistance according to EN 12310-1	300	N
Resistance to static load according to EN 12730 (B)	20	kg
Water tightness according to EN 1928	400	kPa
Artificial ageing according to EN 1297	class 0	-
Folding in the cold according to EN 495-5	-30	°C
Bitumen compatibility according to EN 1548	passed	-
Resistance to root penetration (for green roofs) according to EN 13948 or the German guiding principle FLL	passed	-

Product declarations

Environmental product declarations (EPD):

An EPD is available - see section Mat 01 Life cycle impacts.

Management

Summary

This category encourages the adoption of sustainable management practices in connection with design, construction, commissioning, handover and aftercare activities to ensure that robust sustainability objectives are set and followed through into the operation of the building. Issues in this section focus on embedding sustainability actions through the key stages of design, procurement and initial occupation from the initial project brief stage to the appropriate provision of aftercare.

Category summary table for this BREEAM issue:

Issue ID	Issue name	Relevance for the declared product
Man 01	Project brief and design	No
Man 02	Life cycle cost and service life planning	Yes
Man 03	Responsible construction practices	No
Man 04	Commissioning and handover	No
Man 05	Aftercare	No

Man 02 Life cycle cost and service life planning

Aim of this issue

To deliver whole life value from investment and promote economic sustainability by recognising and encouraging the use and sharing of life cycle costing and service life planning to improve design, specification and through-life maintenance and operation.

Product information for EVALON® V within this issue:

Specific information	Evidence (quality)
Reference service life RSL	<p>> 35 years</p> <p>If exposed to standard load, professionally installed and applied in accordance with the intended use under normal climatic conditions in compliance with the generally accepted engineering standards, the declared products can reach a service life of 35 years and more. If professionally applied under an ecological protection/wearing layer (e. g. green roof) this service life can be still extended.</p> <p>The in-use conditions will be significantly enhanced when installed with alwitra system parts, as the system parts used in the waterproofing such as rainwater outlets, vents, coated metal sheets or rooflights are flashed against the declared membranes in a homogeneous, waterproof connection. The waterproofing of adjacent constructional elements is complemented by additional components of the product system, e.g. roof edge trim and wall connection profiles.</p> <p>If the waterproofing consists of the declared products, it will not be necessary to remove it in case of restoration/refurbishment. In fact, the old waterproofing usually can serve as a substrate for the new refurbishment layer.</p>
Maintenance requirements/ recommendations	<p>Maintenance should include the following tasks:</p> <ul style="list-style-type: none"> - Cleaning the surface by removing dirt, leaves and further unwanted vegetation - Cleaning roof drains and ventilation openings - Gravel drift balancing. <p>Maintenance activities should be executed once or twice per year, depending on the roof pitch, as well as related mechanical, thermal, biological, chemical and further environmental characteristics that influence roofing and aging.</p>
End of life stage	<p>EVALON® membranes are not re-used in their original form after their service life. If sorted, EVALON® membranes can be collected by the ROOFCOLLECT® system (Recycling System for Thermoplastic Membranes). The recycled materials gained from the old roofing membranes can be reintroduced into the cycle of materials, e. g. by usage in inspection walkway tiles. These inspection walkway tiles are used to protect the waterproofing and to mark the maintenance walkways on flat roofs. The textured surface provides a strong grip, even on sloped and wet areas.</p> <p>At the end of service life, thermal utilisation is also possible. The energy contained in the declared products is recovered, thus saving on additional back-up firing in the waste incineration plant.</p>

Additionally, the information provided within the EPD can be used within life cycle costing / planning.

Materials

Summary

This category encourages steps taken to reduce the impact of construction materials through design, construction, maintenance and repair. Issues in this section focus on the procurement of materials that are sourced in a responsible way and have a low embodied impact over their life including extraction, processing and manufacture and recycling.

Category summary table for this BREEAM issue

Issue ID	Issue name	Relevance for the declared product
Mat 01	Life cycle impacts	Yes
Mat 02	Hard landscaping and boundary protection	No
Mat 03	Responsible sourcing of materials	Yes
Mat 04	Insulation	No
Mat 05	Designing for durability and resilience	Yes
Mat 06	Material efficiency	Yes

Mat 01 Life cycle impacts

Aim of this issue

To recognise and encourage the use of construction materials with a low environmental impact (including embodied carbon) over the full life cycle of the building.

Product information for EVALON® V within this issue:

Description	Value	Link
Product specific environmental profile certification available?	yes (product specific EPD)	
EPD Program Operator	Institute Construction and Environment (IBU - Institut Bauen und Umwelt e.V.), Berlin, Germany	www.construction-environment.com
EPD Number	EPD-ALW-20140020-IBA1-EN	http://alwitra.de/wp-content/uploads/2014/07/EPD_ALW_20140020_IBA1_EN.pdf
System boundaries	A1-A5, C2, C3, D (cradle-to-gate with options)	-
PCR	Plastic and elastomer roofing and sealing sheet systems	
Author of the LCA	thinkstep AG, (formerly PE INTERNATIONAL AG), Leinfelden-Echterdingen, Germany	

alwitra GmbH & Co.

Product sustainability fact sheet

Green Guide rating

See closest generic Green Guide ratings for PVC single ply roofing membranes at www.bre.co.uk/greenguide

e.g. Green Guide Element: 1212540003
"Structural steel trusses, galvanised steel purlins and deck, vapour control layer, insulation, PVC single ply waterproofing membrane" with an **A+ summary rating**

Scenarios	Scenario 1: 100% waste incineration at a distance of 50 km Scenario 2: 100% recycling (for production of maintenance walkway tiles) at a distance of 737 km.
-----------	---

Additional information on the installation methods considered in the LCA	Ballast or mechanical fasteners are not included within the LCA results described in this fact sheet. But bonding with alwitra adhesive L40 or with alwitra adhesive PUR D are covered by this fact sheet (see ANNEX).
--	--

The impact indicators resulting from the life cycle assessment, together with resource use and output indicators for 1 m² of waterproofing membrane EVALON® V 1.5 mm mechanically fastened or loose laid under ballast are provided below (ballast or mechanical fasteners are not included within the LCA). Results for EVALON 1.2 mm mechanically fastened or loose laid under ballast and for both products bonded with alwitra adhesive L 40, or bonded with alwitra adhesive PUR D are provided in the annex at the end of this factsheet.

Note: ballast or mechanical fasteners are not included within the LCA results described in this fact sheet.

Results of the LCA – ENVIRONMENTAL IMPACTS:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.5 mm								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE			END OF LIFE STAGE		BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
GWP [kg CO ₂ -eq.]	6.75E+00	3.25E-02	5.10E-01	3.25E-02	3.85E+00	9.51E-01	-2.56E+00	-3.04E+00
ODP [kg CFC11-eq.]	1.41E-08	6.78E-13	7.11E-10	6.78E-13	5.54E-11	5.12E-10	-7.56E-10	-7.24E-09
AP [kg SO ₂ -eq.]	2.51E-02	8.47E-05	1.30E-03	8.47E-05	9.30E-04	1.77E-03	-3.52E-03	-1.14E-02
EP [kg PO ₄ ³⁻ -eq.]	2.98E-03	1.92E-05	1.55E-04	1.92E-05	7.24E-05	2.14E-04	-3.96E-04	-1.38E-03
POCP [kg ethene-eq.]	7.87E-03	-2.42E-05	3.96E-04	-2.42E-05	5.26E-05	6.01E-05	-3.25E-04	-4.06E-03
ADPE [kg Sb eq.]	1.20E-05	1.50E-09	6.04E-07	1.50E-09	5.51E-07	1.42E-07	-2.61E-07	-6.18E-06
ADPF [MJ]	1.45E+02	4.44E-01	7.54E+00	4.44E-01	1.81E+00	9.92E+00	-3.39E+01	-6.90E+01

Caption

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources

alwitra GmbH & Co.

Product sustainability fact sheet

Results of the LCA – RESOURCE USE:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.5 mm								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE			END OF LIFE STAGE		BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
PE total [MJ]	1,72E+02	4,71E-01	8,94E+00	4,71E-01	2,22E+00	1,65E+01	-4,28E+01	-8,06E+01
PERE [MJ]	1.47E+01	2.64E-02	7.62E-01	2.64E-02	1.73E-01	2.5E+00	-3.64E+00	-6.6E+00
PERM [MJ]	0	-	-	-	-	-	-	-
PERT [MJ]	1.47E+01	2.64E-02	7.62E-01	2.64E-02	1.73E-01	2.5E+00	-3.64E+00	-6.6E+00
PENRE [MJ]	1.05E+02	4.45E-01	8.18E+00	4.45E-01	2.05E+00	1.4E+01	-3.92E+01	-7.4E+01
PENRM [MJ]	5.22E+01	-	-	-	-	-	-	-
PENRT [MJ]	1.57E+02	4.45E-01	8.18E+00	4.45E-01	2.05E+00	1.4E+01	-3.92E+01	-7.4E+01
SM [kg]	0	-	-	-	-	-	-	-
RSF [MJ]	0	0	0	0	0	0	0	0
NRSF [MJ]	0	0	0	0	0	0	0	0
FW [m ³]	9.52E-02	2.54E-05	5.26E-03	2.54E-05	9.46E-03	3.7E-03	-5.68E-03	-4.9E-02

Caption

PE total = Total use of primary energy resources (=PERT+PENRT); PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

Product sustainability fact sheet

Results of the LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.5 mm								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE		END OF LIFE STAGE			BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
HWD [kg]	1.26E-02	0.00E+00	1.25E-03	0.00E+00	9.92E-02	0.00E+00	0.00E+00	-5.35E-03
NHWD [kg]	4.46E-01	8.80E-05	2.24E-02	8.80E-05	7.85E-04	8.24E-03	-1.43E-02	-2.29E-01
RWD [kg]	4.83E-03	6.39E-07	2.55E-04	6.39E-07	9.89E-05	1.48E-03	-2.17E-03	-2.12E-03
CRU [kg]	0	0	0	0	0	0	-	-
MFR [kg]	0	0	0	0	0.00E+00	2.10E+00	-	-
MER [kg]	0	0	0	0	2.10E+00	0.00E+00	-	-
EEE [MJ]	-	-	-	-	-	-	7.63E+00	2.12E-01
EET [MJ]	-	-	-	-	-	-	1.83E+01	5.11E-01

Caption

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier; EEE = Exported energy, electric energy, EET = Exported energy, thermal energy

Mat 03 Responsible sourcing of materials

Aim of this issue

To recognise and encourage the specification and procurement of responsibly sourced materials for key building elements.

Product information for EVALON® V within this issue:

Responsible Sourcing Certification Scheme	Certification level / scope
EN ISO 9001: 2008	<p>The quality management system of alwitra GmbH & Co. Klaus Göbel has been certified according to ISO 9001 by TÜV Rheinland Cert GmbH (Certificate 011005463). The certificate is available online, see http://alwitra.de/wp-content/uploads/2014/02/zertifikat-iso-9001_2008_2015-deutsch.pdf.</p> <p>The suppliers of the most important raw materials (regarding mass contribution) are also certified according to ISO 9001.</p>
EN ISO 14001: 2004	<p>The environmental management system of alwitra GmbH & Co. Klaus Göbel has been certified according to ISO 14001 by TÜV Rheinland Cert GmbH (Certificate 01104000580). The certificate is available online, see http://alwitra.de/wp-content/uploads/2014/02/zertifikat-iso-14001_2004_2015-deutsch.pdf.</p> <p>The suppliers of the most important raw materials (regarding mass contribution) are also certified according to ISO 9001.</p>
ISO 50001: 2011	<p>The energy management system of alwitra GmbH & Co. Klaus Göbel has been certified according to ISO 50001 by TÜV Rheinland Cert GmbH (Certificate 014075463). The certificate is available online, see http://alwitra.de/wp-content/uploads/2014/02/zertifikat-iso-50001_2011_2015-deutsch.pdf.</p>

Product sustainability fact sheet

Responsible sourcing certification scheme point scores

A graded scale to reflect the rigour of the certification scheme used to demonstrate responsible sourcing, forming the basis for awarding credits in the BREEAM issue Mat 03. Refer to Guidance Note (TBC) available in the Resources section of the BREEAM website for an up-to-date table of responsible sourcing certification schemes recognised by BRE Global Ltd for the purposes of a BREEAM assessment.

Detailed information [Mat 03 Responsible sourcing of materials](#) and <http://www.breeam.org/page.jsp?id=617>

Mat 05 Designing for durability and resilience

Aim of this issue

To recognise and encourage adequate protection of exposed elements of the building and landscape, therefore minimising the frequency of replacement and maximising materials optimisation.

Product information for EVALON® V within this issue:

Item	Description	Evidence (quality)
Durability improvement	The roofing membranes are designed to last more than 35 years.	See above in "Mat 02" the description of the product.

Mat 06 Material efficiency

Aim of this issue

To recognise and encourage measures to optimise material efficiency in order to minimise environmental impact of material use and waste.

Product information for EVALON® V within this issue:

Specific information
The product is delivered at standard width and is cut during installation in a way that there are no significant material losses. Offcuts during production are internally recycled to 100 % to achieve a high material efficiency.
Using it for a green roof, the membrane provides both waterproofing and root protection in a single product.

Pollution

Summary

This category addresses the prevention and control of pollution and surface water run-off associated with the building's location and use. Issues in this section aim to reduce the buildings impact on surrounding communities and environments arising from light-pollution, noise, flooding and emissions to air, land and water.

Category summary table for this BREEAM issue

Issue ID	Issue name	Relevance for the declared product
Pol 01	Impact of refrigerants	No
Pol 02	NO _x emissions	No
Pol 03	Surface water run-off	Yes
Pol 04	Reduction of night time light pollution	No
Pol 05	Reduction of noise pollution	No

Product sustainability fact sheet

Pol 03 Surface water run-off

Aim of this issue

To avoid, reduce and delay the discharge of rainfall to public sewers and watercourses, thereby minimising the risk and impact of localised flooding on and off-site, watercourse pollution and other environmental damage.

A green roof reduces the speed and amount of water run-off. EVALON® V is resistant to root/rhizome penetration and can therefore be used for green roofs as a waterproofing membrane providing protection against root penetration at the same time.

Waste

Summary

This category encourages the sustainable management (and reuse where feasible) of construction, operational waste and waste through future maintenance and repairs associated with the building structure. By encouraging good design and construction practices, issues in this section aim to reduce the waste arising from the construction and operation of the building, encouraging its diversion from landfill. It includes recognition of measures to reduce future waste as a result of the need to alter the building in the light of future changes to climate.

Category summary table for this BREEAM issue

Issue ID	Issue name	Relevance for the declared product
Wst 01	Construction waste management	Yes
Wst 02	Recycled aggregates	No
Wst 03	Operational waste	No
Wst 04	Speculative floor and ceiling finishes	No
Wst 05	Adaptation to climate change	No
Wst 06	Functional adaptability	No

Wst 01 Construction waste management

Aim of this issue

To promote resource efficiency via the effective management and reduction of construction waste.

Product information for the declared product within this issue:

Specific information

After the use phase, the membranes are collected and recycled within the ROOFCOLLECT® Recycling System for Thermoplastic Membranes.

When repair activities are required, it is generally possible to rebuild the sealing function (waterproofing) made of EVALON membranes. Therefore, new EVALON strips are used and fitted by welding techniques according to the manufacturer's guidelines/installation manual.

Disclaimer

The content of, and results shown in this report are based on data and information submitted by the client. Therefore, thinkstep AG makes no representation or warranty, express or implied, in regard of the correctness or completeness of the content of this document or the results shown.

ANNEX

EVALON® V 1.2 mm, mechanically fastened or loose laid under ballast

The impact indicators resulting from the life cycle assessment, together with resource use and output indicators for 1 m² installed waterproofing membrane EVALON® V 1.2 mm, mechanically fastened or loose laid under ballast are provided below.

Note: ballast or mechanical fasteners are not included within the LCA results described in this fact sheet.

Results of the LCA – ENVIRONMENTAL IMPACTS:

Declared unit: 1 m² of waterproofing membrane EVALON® V 1.2 mm								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE			END OF LIFE STAGE		BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
GWP [kg CO ₂ -eq.]	5.56E+00	2.65E-02	4.22E-01	2.65E-02	3.13E+00	7.75E-01	-2.09E+00	-2.47E+00
ODP [kg CFC11-eq.]	1.13E-08	5.52E-13	5.71E-10	5.52E-13	4.51E-11	4.17E-10	-6.16E-10	-5.89E-09
AP [kg SO ₂ -eq.]	2.03E-02	6.90E-05	1.06E-03	6.90E-05	7.57E-04	1.44E-03	-2.87E-03	-9.26E-03
EP [kg PO ₄ ³⁻ -eq.]	2.41E-03	1.57E-05	1.26E-04	1.57E-05	5.89E-05	1.74E-04	-3.22E-04	-1.12E-03
POCP [kg ethene-eq.]	6.36E-03	-1.97E-05	6.16E-04	-1.97E-05	4.28E-05	4.89E-05	-2.65E-04	-3.31E-03
ADPE [kg Sb eq.]	9.64E-06	1.22E-09	4.86E-07	1.22E-09	4.49E-07	1.16E-07	-2.13E-07	-5.04E-06
ADPF [MJ]	1.20E+02	3.62E-01	6.25E+00	3.62E-01	1.47E+00	8.08E+00	-2.76E+01	-5.62E+01

Caption

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources

alwitra GmbH & Co.

Product sustainability fact sheet

Results of the LCA – RESOURCE USE:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.2 mm								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE			END OF LIFE STAGE		BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
PE total [MJ]	1.41E+02	3.85E-01	7.39E+00	3.85E-01	1.81E+00	1.31E+01	-3.49E+01	-6.63E+01
PERE [MJ]	1.19E+01	2.15E-02	6.20E-01	2.15E-02	1.40E-01	2.10E+00	-2.96E+00	-5.30E+00
PERM [MJ]	0.00E+00	-	-	-	-	-	-	-
PERT [MJ]	1.19E+01	2.15E-02	6.20E-01	2.15E-02	1.40E-01	2.10E+00	-2.96E+00	-5.30E+00
PENRE [MJ]	8.64E+01	3.63E-01	6.77E+00	3.63E-01	1.67E+00	1.10E+01	-3.19E+01	-6.10E+01
PENRM [MJ]	4.26E+01	-	-	-	-	-	-	-
PENRT [MJ]	1.29E+02	3.63E-01	6.77E+00	3.63E-01	1.67E+00	1.10E+01	-3.19E+01	-6.10E+01
SM [kg]	0.00E+00	-	-	-	-	-	-	-
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW [m ³]	7.79E-02	2.07E-05	4.26E-03	2.07E-05	7.70E-03	3.00E-03	-4.62E-03	-4.00E-02

Caption

PE total = Total use of primary energy resources (=PERT+PENRT); PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

Product sustainability fact sheet

Results of the LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.2 mm								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE		END OF LIFE STAGE			BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
HWD [kg]	1.06E-02	0.00E+00	1.04E-03	0.00E+00	8.08E-02	0.00E+00	0.00E+00	-4.35E-03
NHWD [kg]	3.58E-01	7.18E-05	1.80E-02	7.18E-05	6.40E-04	6.71E-03	-1.16E-02	-1.87E-01
RWD [kg]	3.97E-03	5.21E-07	2.12E-04	5.21E-07	8.05E-05	1.20E-03	-1.77E-03	-1.73E-03
CRU [kg]	0	0	0	0	0	0	-	-
MFR [kg]	0	0	0	0	0.00E+00	1.71E+00	-	-
MER [kg]	0	0	0	0	1.71E+00	0.00E+00	-	-
EEE [MJ]	-	-	-	-	-	-	6.21E+00	1.73E-01
EET [MJ]	-	-	-	-	-	-	1.49E+01	4.17E-01

Caption

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier; EEE = Exported energy, electric energy, EET = Exported energy, thermal energy

EVALON® V 1.2 mm - bonded with alwitra adhesive L 40

The impact indicators resulting from the life cycle assessment, together with resource use and output indicators for 1 m² installed waterproofing membrane EVALON® V 1.2 mm - bonded with alwitra adhesive L 40 are provided below.

Results of the LCA – ENVIRONMENTAL IMPACTS:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.2 mm, bonded with L40								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE		END OF LIFE STAGE			BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
GWP [kg CO ₂ -eq.]	5.56E+00	2.65E-02	9.82E-01	2.65E-02	3.13E+00	7.75E-01	-2.09E+00	-2.47E+00
ODP [kg CFC11-eq.]	1.13E-08	5.52E-13	6.11E-10	5.52E-13	4.51E-11	4.17E-10	-6.16E-10	-5.89E-09
AP [kg SO ₂ -eq.]	2.03E-02	6.90E-05	2.38E-03	6.90E-05	7.57E-04	1.44E-03	-2.87E-03	-9.26E-03
EP [kg PO ₄ ³⁻ -eq.]	2.43E-03	1.57E-05	2.35E-04	1.57E-05	5.89E-05	1.74E-04	-3.22E-04	-1.12E-03
POCP [kg ethene-eq.]	6.46E-03	-1.97E-05	1.42E-01	-1.97E-05	4.28E-05	4.89E-05	-2.65E-04	-3.31E-03
ADPE [kg Sb eq.]	9.64E-06	1.22E-09	2.72E-05	1.22E-09	4.49E-07	1.16E-07	-2.13E-07	-5.04E-06
ADPF [MJ]	1.20E+02	3.62E-01	2.58E+01	3.62E-01	1.47E+00	8.08E+00	-2.76E+01	-5.62E+01

Caption

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources

alwitra GmbH & Co.

Product sustainability fact sheet

Results of the LCA – RESOURCE USE:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.2 mm, bonded with L40								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE			END OF LIFE STAGE		BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
PE total [MJ]	1.41E+02	3.85E-01	2.74E+01	3.85E-01	1.81E+00	1.31E+01	-3.49E+01	-6.63E+01
PERE [MJ]	1.19E+01	2.15E-02	8.33E-01	2.15E-02	1.40E-01	2.10E+00	-2.96E+00	-5.30E+00
PERM [MJ]	0.00E+00	-	-	-	-	-	-	-
PERT [MJ]	1.19E+01	2.15E-02	8.33E-01	2.15E-02	1.40E-01	2.10E+00	-2.96E+00	-5.30E+00
PENRE [MJ]	8.64E+01	3.63E-01	2.66E+01	3.63E-01	1.67E+00	1.10E+01	-3.19E+01	-6.10E+01
PENRM [MJ]	4.26E+01	-	-	-	-	-	-	-
PENRT [MJ]	1.29E+02	3.63E-01	2.66E+01	3.63E-01	1.67E+00	1.10E+01	-3.19E+01	-6.10E+01
SM [kg]	0.00E+00	-	-	-	-	-	-	-
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW [m ³]	7.68E-02	2.07E-05	5.71E-03	2.07E-05	7.70E-03	3.00E-03	-4.62E-03	-4.00E-02

Caption

PE total = Total use of primary energy resources (=PERT+PENRT); PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

alwitra GmbH & Co.

Product sustainability fact sheet

Results of the LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.2 mm, bonded with L40								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE		END OF LIFE STAGE			BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
HWD [kg]	1.06E-02	0.00E+00	1.52E-03	0.00E+00	8.08E-02	0.00E+00	0.00E+00	-4.35E-03
NHWD [kg]	3.58E-01	7.18E-05	2.00E-02	7.18E-05	6.40E-04	6.71E-03	-1.16E-02	-1.87E-01
RWD [kg]	3.97E-03	5.21E-07	3.26E-04	5.21E-07	8.05E-05	1.20E-03	-1.77E-03	-1.73E-03
CRU [kg]	0	0	0	0	0	0	-	-
MFR [kg]	0	0	0	0	0.00E+00	1.71E+00	-	-
MER [kg]	0	0	0	0	1.71E+00	0.00E+00	-	-
EEE [MJ]	-	-	-	-	-	-	6.21E+00	1.73E-01
EET [MJ]	-	-	-	-	-	-	1.49E+01	4.17E-01

Caption

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier; EEE = Exported energy, electric energy, EET = Exported energy, thermal energy

EVALON® V 1.5 mm – bonded with alwitra adhesive L 40

The impact indicators resulting from the life cycle assessment, together with resource use and output indicators for 1 m² of waterproofing membrane EVALON® V 1.5 mm – bonded with alwitra adhesive L 40 are provided below.

Results of the LCA – ENVIRONMENTAL IMPACTS:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.5 mm bonded with alwitra adhesive L 40								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE		END OF LIFE STAGE			BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
GWP [kg CO ₂ -eq.]	6.75E+00	3.25E-02	1.07E+00	3.25E-02	3.85E+00	9.51E-01	-2.56E+00	-3.04E+00
ODP [kg CFC11-eq.]	1.41E-08	6.78E-13	7.51E-10	6.78E-13	5.54E-11	5.12E-10	-7.56E-10	-7.24E-09
AP [kg SO ₂ -eq.]	2.51E-02	8.47E-05	2.62E-03	8.47E-05	9.30E-04	1.77E-03	-3.52E-03	-1.14E-02
EP [kg PO ₄ ³⁻ -eq.]	3.01E-03	1.92E-05	2.65E-04	1.92E-05	7.24E-05	2.14E-04	-3.96E-04	-1.38E-03
POCP [kg ethene-eq.]	8.00E-03	-2.42E-05	1.42E-01	-2.42E-05	5.26E-05	6.01E-05	-3.25E-04	-4.06E-03
ADPE [kg Sb eq.]	1.20E-05	1.50E-09	2.74E-05	1.50E-09	5.51E-07	1.42E-07	-2.61E-07	-6.18E-06
ADPF [MJ]	1.45E+02	4.44E-01	2.71E+01	4.44E-01	1.81E+00	9.92E+00	-3.39E+01	-6.90E+01

Caption

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources

alwitra GmbH & Co.

Product sustainability fact sheet

Results of the LCA – RESOURCE USE:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.5 mm bonded with alwitra adhesive L 40								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE			END OF LIFE STAGE		BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
PE total [MJ]	1,72E+02	4,71E-01	2,90E+01	4,71E-01	2,22E+00	1,65E+01	-4,28E+01	-8,06E+01
PERE [MJ]	1,47E+01	2,64E-02	9,71E-01	2,64E-02	1,73E-01	2,50E+00	-3,64E+00	-6,60E+00
PERM [MJ]	0,00E+00	-	-	-	-	-	-	-
PERT [MJ]	1,47E+01	2,64E-02	9,71E-01	2,64E-02	1,73E-01	2,50E+00	-3,64E+00	-6,60E+00
PENRE [MJ]	1,05E+02	4,45E-01	2,80E+01	4,45E-01	2,05E+00	1,40E+01	-3,92E+01	-7,40E+01
PENRM [MJ]	5,22E+01	-	-	-	-	-	-	-
PENRT [MJ]	1,57E+02	4,45E-01	2,80E+01	4,45E-01	2,05E+00	1,40E+01	-3,92E+01	-7,40E+01
SM [kg]	0,00E+00	-	-	-	-	-	-	-
RSF [MJ]	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
NRSF [MJ]	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00	0,00E+00
FW [m ³]	9,52E-02	2,54E-05	6,71E-03	2,54E-05	9,46E-03	3,70E-03	-5,68E-03	-4,90E-02

Caption

PE total = Total use of primary energy resources (=PERT+PENRT); PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

alwitra GmbH & Co.

Product sustainability fact sheet

Results of the LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.5 mm bonded with alwitra adhesive L 40								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE		END OF LIFE STAGE			BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
HWD [kg]	1.26E-02	0.00E+00	1.73E-03	0.00E+00	9.92E-02	0.00E+00	0.00E+00	-5.35E-03
NHWD [kg]	4.46E-01	8.80E-05	2.44E-02	8.80E-05	7.85E-04	8.24E-03	-1.43E-02	-2.29E-01
RWD [kg]	4.83E-03	6.39E-07	3.69E-04	6.39E-07	9.89E-05	1.48E-03	-2.17E-03	-2.12E-03
CRU [kg]	0	0	0	0	0	0	-	-
MFR [kg]	0	0	0	0	0.00E+00	2.10E+00	-	-
MER [kg]	0	0	0	0	2.10E+00	0.00E+00	-	-
EEE [MJ]	-	-	-	-	-	-	7.63E+00	2.12E-01
EET [MJ]	-	-	-	-	-	-	1.83E+01	5.11E-01

Caption

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier; EEE = Exported energy, electric energy, EET = Exported energy, thermal energy

EVALON® V 1.2 mm - bonded with alwitra adhesive PUR D

The impact indicators resulting from the life cycle assessment, together with resource use and output indicators for 1 m² of waterproofing membrane EVALON® V 1.2 mm - bonded with alwitra adhesive PUR D are provided below.

Results of the LCA – ENVIRONMENTAL IMPACTS:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.2 mm - bonded with alwitra adhesive PUR D								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE		END OF LIFE STAGE			BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
GWP [kg CO ₂ -eq.]	5.56E+00	2.65E-02	1.07E+00	2.65E-02	3.13E+00	7.75E-01	-2.09E+00	-2.47E+00
ODP [kg CFC11-eq.]	1.13E-08	5.52E-13	6.79E-10	5.52E-13	4.51E-11	4.17E-10	-6.16E-10	-5.89E-09
AP [kg SO ₂ -eq.]	2.03E-02	6.90E-05	2.21E-03	6.90E-05	7.57E-04	1.44E-03	-2.87E-03	-9.26E-03
EP [kg PO ₄ ³⁻ -eq.]	2.43E-03	1.57E-05	2.85E-04	1.57E-05	5.89E-05	1.74E-04	-3.22E-04	-1.12E-03
POCP [kg ethene-eq.]	6.46E-03	-1.97E-05	4.28E-03	-1.97E-05	4.28E-05	4.89E-05	-2.65E-04	-3.31E-03
ADPE [kg Sb eq.]	9.64E-06	1.22E-09	2.58E-06	1.22E-09	4.49E-07	1.16E-07	-2.13E-07	-5.04E-06
ADPF [MJ]	1.20E+02	3.62E-01	1.95E+01	3.62E-01	1.47E+00	8.08E+00	-2.76E+01	-5.62E+01

Caption

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources

alwitra GmbH & Co.

Product sustainability fact sheet

Results of the LCA – RESOURCE USE:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.2 mm - bonded with alwitra adhesive PUR D								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE			END OF LIFE STAGE		BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
PE total [MJ]	1.41E+02	3.85E-01	2.18E+01	3.85E-01	1.81E+00	1.31E+01	-3.49E+01	-6.63E+01
PERE [MJ]	1.19E+01	2.15E-02	1.13E+00	2.15E-02	7.27E-02	2.10E+00	-7.19E-01	-5.30E+00
PERM [MJ]	0.00E+00	-	-	-	-	-	-	-
PERT [MJ]	1.19E+01	2.15E-02	1.13E+00	2.15E-02	1.40E-01	2.10E+00	-2.96E+00	-5.30E+00
PENRE [MJ]	8.64E+01	3.63E-01	2.07E+01	3.63E-01	1.67E+00	1.10E+01	-3.19E+01	-6.10E+01
PENRM [MJ]	4.26E+01	-	-	-	-	-	-	-
PENRT [MJ]	1.29E+02	3.63E-01	2.07E+01	3.63E-01	1.67E+00	1.10E+01	-3.19E+01	-6.10E+01
SM [kg]	0.00E+00	-	-	-	-	-	-	-
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW [m ³]	7.68E-02	2.07E-05	7.42E-03	2.07E-05	7.70E-03	3.00E-03	-4.62E-03	-4.00E-02

Caption

PE total = Total use of primary energy resources (=PERT+PENRT); PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

alwitra GmbH & Co.

Product sustainability fact sheet

Results of the LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.2 mm - bonded with alwitra adhesive PUR D								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE		END OF LIFE STAGE			BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
HWD [kg]	1.06E-02	0.00E+00	2.48E-03	0.00E+00	8.08E-02	0.00E+00	0.00E+00	-4.35E-03
NHWD [kg]	3.58E-01	7.18E-05	2.46E-02	7.18E-05	6.40E-04	6.71E-03	-1.16E-02	-1.87E-01
RWD [kg]	3.97E-03	5.21E-07	5.17E-04	5.21E-07	8.05E-05	1.20E-03	-1.77E-03	-1.73E-03
CRU [kg]	0	0	0	0	0	0	-	-
MFR [kg]	0	0	0	0	0.00E+00	1.71E+00	-	-
MER [kg]	0	0	0	0	1.71E+00	0.00E+00	-	-
EEE [MJ]	-	-	-	-	-	-	6.21E+00	1.73E-01
EET [MJ]	-	-	-	-	-	-	1.49E+01	4.17E-01

Caption

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier; EEE = Exported energy, electric energy, EET = Exported energy, thermal energy

EVALON® V 1.5 mm - bonded with alwitra adhesive PUR D

The impact indicators resulting from the life cycle assessment, together with resource use and output indicators for 1 m² of waterproofing membrane EVALON® V 1.5 mm - bonded with alwitra adhesive PUR D are provided below.

Results of the LCA – ENVIRONMENTAL IMPACTS:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.5 mm - bonded with alwitra adhesive PUR D								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE		END OF LIFE STAGE			BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
GWP [kg CO ₂ -eq.]	6.74E+00	3.25E-02	1.15E+00	3.25E-02	3.85E+00	9.51E-01	-2.56E+00	-3.04E+00
ODP [kg CFC11-eq.]	1.41E-08	6.78E-13	8.19E-10	6.78E-13	5.54E-11	5.12E-10	-7.56E-10	-7.24E-09
AP [kg SO ₂ -eq.]	2.51E-02	8.47E-05	2.45E-03	8.47E-05	9.30E-04	1.77E-03	-3.52E-03	-1.14E-02
EP [kg PO ₄ ³⁻ -eq.]	3.01E-03	1.92E-05	3.14E-04	1.92E-05	7.24E-05	2.14E-04	-3.96E-04	-1.38E-03
POCP [kg ethene-eq.]	8.00E-03	-2.42E-05	4.36E-03	-2.42E-05	5.26E-05	6.01E-05	-3.25E-04	-4.06E-03
ADPE [kg Sb eq.]	1.20E-05	1.50E-09	2.70E-06	1.50E-09	5.51E-07	1.42E-07	-2.61E-07	-6.18E-06
ADPF [MJ]	1.45E+02	4.44E-01	2.08E+01	4.44E-01	1.81E+00	9.92E+00	-3.39E+01	-6.90E+01

Caption

GWP = Global warming potential; ODP = Depletion potential of the stratospheric ozone layer; AP = Acidification potential of land and water; EP = Eutrophication potential; POCP = Formation potential of tropospheric ozone photochemical oxidants; ADPE = Abiotic depletion potential for non-fossil resources; ADPF = Abiotic depletion potential for fossil resources

alwitra GmbH & Co.

Product sustainability fact sheet

Results of the LCA – RESOURCE USE:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.5 mm - bonded with alwitra adhesive PUR D								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE			END OF LIFE STAGE		BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
PE total [MJ]	1.72E+02	4.71E-01	2.34E+01	4.71E-01	2.22E+00	1.65E+01	-4.28E+01	-8.06E+01
PERE [MJ]	1.47E+01	2.64E-02	1.27E+00	2.64E-02	1.73E-01	2.50E+00	-3.64E+00	-6.60E+00
PERM [MJ]	0.00E+00	-	-	-	-	-	-	-
PERT [MJ]	1.47E+01	2.64E-02	1.27E+00	2.64E-02	1.73E-01	2.50E+00	-3.64E+00	-6.60E+00
PENRE [MJ]	1.05E+02	4.45E-01	2.21E+01	4.45E-01	2.05E+00	1.40E+01	-3.92E+01	-7.40E+01
PENRM [MJ]	5.22E+01	-	-	-	-	-	-	-
PENRT [MJ]	1.57E+02	4.45E-01	2.21E+01	4.45E-01	2.05E+00	1.40E+01	-3.92E+01	-7.40E+01
SM [kg]	0.00E+00	-	-	-	-	-	-	-
RSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
NRSF [MJ]	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00	0.00E+00
FW [m ³]	9.67E-02	2.54E-05	8.48E-03	2.54E-05	9.46E-03	3.70E-03	-5.68E-03	-4.90E-02

Caption

PE total = Total use of primary energy resources (=PERT+PENRT); PERE = Use of renewable primary energy excluding renewable primary energy resources used as raw materials; PERM = Use of renewable primary energy resources used as raw materials; PERT = Total use of renewable primary energy resources; PENRE = Use of non-renewable primary energy excluding non-renewable primary energy resources used as raw materials; PENRM = Use of non-renewable primary energy resources used as raw materials; PENRT = Total use of non-renewable primary energy resources; SM = Use of secondary material; RSF = Use of renewable secondary fuels; NRSF = Use of non-renewable secondary fuels; FW = Use of net fresh water

alwitra GmbH & Co.

Product sustainability fact sheet

Results of the LCA – OUTPUT FLOWS AND WASTE CATEGORIES:

Declared unit: 1 m ² of waterproofing membrane EVALON® V 1.5 mm - bonded with alwitra adhesive PUR D								
Declared life cycle stages (standard DIN EN 15978)	PRODUCT STAGE	CONSTRUCTION PROCESS STAGE		END OF LIFE STAGE			BENEFITS AND LOADS BEYOND THE SYSTEM BOUNDARYS	
	A1-A3	A4	A5	C2	C3/1	C3/2	D/1	D/2
HWD [kg]	1.26E-02	0.00E+00	2.69E-03	0.00E+00	9.92E-02	0.00E+00	0.00E+00	-5.35E-03
NHWD [kg]	4.46E-01	8.80E-05	2.90E-02	8.80E-05	7.85E-04	8.24E-03	-1.43E-02	-2.29E-01
RWD [kg]	4.83E-03	6.39E-07	5.60E-04	6.39E-07	9.89E-05	1.48E-03	-2.17E-03	-2.12E-03
CRU [kg]	0	0	0	0	0	0	-	-
MFR [kg]	0	0	0	0	0.00E+00	2.10E+00	-	-
MER [kg]	0	0	0	0	2.10E+00	0.00E+00	-	-
EEE [MJ]	-	-	-	-	-	-	7.63E+00	2.12E-01
EET [MJ]	-	-	-	-	-	-	1.83E+01	5.11E-01

Caption

HWD = Hazardous waste disposed; NHWD = Non-hazardous waste disposed; RWD = Radioactive waste disposed; CRU = Components for re-use; MFR = Materials for recycling; MER = Materials for energy recovery; EE = Exported energy per energy carrier; EEE = Exported energy, electric energy, EET = Exported energy, thermal energy